

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Martin LANG  
Wolfgang REUTER  
Horst BESSERER

Title: MOUNTING PLATE FOR  
ELECTRONIC COMPONENTS

Based Upon: PCT/EP2005/003693

Express Mail No.: EV785681734US

Date of Deposit: 19 July 2006

Customer No.: 42419

**TRANSMITTAL OF SUBSTITUTE SPECIFICATION**

**Mail Stop PCT**  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Dear Sir:

Applicants have enclosed a Substitute Specification attached to a red ink marked-up copy of the verified English language translation of PCT International Application PCT/EP2005/003693. The red ink identifies changes to the verified English language translation which are incorporated in the Substitute Specification.


The Substitute Specification includes general revisions to correct idiomatic translational errors and to provide proper headings. The undersigned states that the Substitute Specification contains no new matter.

10/586425

Based Upon: PCT/EP2005/003693

Applicants sincerely believe that this Patent Application is now in  
condition for prosecution before the U.S. Patent and Trademark Office.

Respectfully submitted,

  
Douglas H. Pauley  
Registration No. 33,295

Pauley Petersen & Erickson  
2800 West Higgins Road; Suite 365  
Hoffman Estates, Illinois 60195  
TEL (847) 490-1400  
FAX (847) 490-1403

1802003693

Based Upon: PCT/EP2005/003693  
Customer No.: 42419

## **SUBSTITUTE SPECIFICATION**

Based Upon: PCT/EP2005/003693

**Customer No.: 42419**

**MOUNTING PLATE FOR ELECTRONIC COMPONENTS**

Based Upon: PCT/EP2005/003693

## **BACKGROUND OF THE INVENTION**

### **Field of the Invention**

This invention relates to a mounting plate for electronic components, having coolant lines integrated in a plate body for cooling fluid to flow through, wherein a fastening arrangement for mounting electronic components to be cooled is arranged on the plate body.

### **Discussion of Related Art**

It is known to install cooling coils in a mounting plate or a mounting board for cooling electronic devices, for example frequency converters, which are to be mounted on the mounting plate. The waste heat from the electronic components can be removed by a so-called "cold plate".

The electronic components can be held on a known mounting plate by screw connections. Screw holes are thus provided in the housings of the electronic components, through which a screw can be screwed into threaded holes to be cut into the mounting plate. However, holes cannot be cut into the known mounting plates without the danger of damage to the cooling coils. The electronic components often have varied dimensions, so that different fastening dimensions also exist. It is often not possible to provide the mounting plate with a prefabricated grid of threaded holes, because the threaded holes arranged on the housings of the electronic components are not aligned with the other threaded holes.

In known mounting plates of the PADA Engineering company, cooling coils are placed so they are visible from the plate surface in order to prevent accidental damage of the coolant conduits during the subsequent mechanical processing of the mounting plate.

However, it is necessary in connection with the known mounting plates to cut specially arranged threaded bores, depending on the fastening dimensions of the electronic components to be mounted. This is expensive from a manufacturing technology standpoint.

The packing density of several electronic components to be mounted is also reduced by the mounting areas prescribed by the position of the cooling coils, because not every location is suitable for drilling a threaded hole due to the layout of the coolant lines.

### **SUMMARY OF THE INVENTION**

It is one object of this invention to provide a mounting plate for electronic components which, along with a reduced mounting cost outlay, assures the secure holding of electronic components to be mounted, and dependably prevents damage to the coolant lines. In addition, the mounting plate in accordance with this invention can make possible the greatest possible packing density of the electronic components.

This object of this invention is achieved with a fastening arrangement having the characteristics described in this specification and in the claims.

Accordingly, the fastening arrangement has at least one first groove embodied to be C-shaped in cross section and that extends in a straight line in the extension direction of the mounting plate, into which at least one screw nut for forming a screw connection with an electronic component can be inserted and fixed against relative rotation. The additional cutting of threaded holes is avoided by this arrangement. Mounting can be simply performed, wherein the matching to the structural conditions of the component housings is possible because of the arbitrarily possible positioning of the screw nut.

In accordance with one consideration, the fastening arrangement can have at least one second groove, which is designed identically to the first groove and which extends parallel with the first groove, whose distance from the first groove is substantially determined by a length of extension perpendicularly with respect to the first and second grooves of the electronic component to be mounted. It is thus assured that, with a preset fastening dimension of electronic components to be mounted, simple securing on the mounting plate can take place.

In accordance with one embodiment, the fastening arrangement can have a further groove, which is embodied identically to the first and the second grooves and that extends parallel with the second groove and which extends at the

side of the second groove facing away from the electronic component to be mounted at a distance which is less than the distance between the first groove and the second groove. With this arrangement, an additional fastening dimension of electronic components to be mounted is taken into account.

Electronic components can be mounted in a simple manner, which have screw holes at distance from each other that corresponds to the distance of the second groove from the first groove, or to the still further groove from the second groove. In this way the electronic components can be directly fastened by screws in the screw nuts inserted into the grooves.

However, in case the fastening dimensions of the electronic components to be mounted do not agree with the distances between the parallel extending grooves, such as if the electronic components to be mounted have screw holes whose distance from each other is less than the distance of the second groove from the first groove, or less than the distance of the still further groove from the first groove, then the component can be fixed in place at least on one side by an angle bracket, wherein at least one screw engaging the angle bracket is screwed into the screw nut introduced into the respective groove.

Here, the angle bracket can have a level base plate for placement against the mounting plate and a clamping area angled off with respect to it for the clamping



fixation of the electronic component to be mounted. In this case, the clamping area can clampingly act on a protrusion provided on the electronic component.

For achieving a particularly simple matching to different fastening dimensions of electronic components to be mounted, the angle bracket can have at least one elongated hole extending perpendicularly with respect to the extension direction of the second groove or of the still further groove for receiving the screw.

In one embodiment the screw nut can be a spring nut.

With regard to manufacturing technology, it can be advantageous if the first groove, the second groove and/or the still further groove are made of one piece with the plate body.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

This invention is explained in greater detail in view of a preferred embodiment, making reference to the drawings, wherein:

Fig. 1 shows in a schematic and perspective lateral view a mounting plate without electronic components to be mounted on it and to be cooled;

Fig. 2 shows in a schematic and perspective lateral view an angle bracket for mounting, which can be matched to various fastening dimensions, of electronic components to be mounted; and

Fig. 3 shows in a schematic and perspective lateral view the mounting plate in accordance with Fig. 1 with electronic components to be mounted on it and to be cooled, each of which is clampingly held on one side by an angle bracket, in accordance with Fig. 2.

### **DETAILED DESCRIPTION OF THE INVENTION**

In a schematic and perspective lateral view, Fig. 1 shows a mounting plate 10 without electronic components to be mounted on it and to be cooled. The mounting plate 10 has a level plate body 14 made of aluminum, in which a coolant line with connectors 16 and 18 in the form of a cooling coil, not shown, is formed for coolant flow. In the area into which the coolant coil is integrally placed, the plate body 14 is not additionally machined and is shaped flat and level. On the right side in Fig. 1 of the area into which the coolant coil has been integrally placed, a first groove 20, which is embodied to be approximately C-shaped in cross section and extends straight in the extension direction (arrow A) of the mounting plate 10, is formed in one piece with the plate body. At least one spring nut (not shown) for forming a screw connection with an electronic component can be introduced, fixed against relative rotation, into the first groove 20. The electronic components to be attached can then be screwed together with the nut.

A second groove 22 extends parallel with the first groove 20 on the side of the plate body at the left in Fig. 1, into which the coolant coil is integrally placed. The distance B between the first groove 20 and the second groove is determined by the area of the plate body into which the coolant coil is integrally placed, and also by the extension length, running perpendicularly with respect to the first groove 20 and the second groove 22, of an electronic component.

A further groove 24 extends parallel with the first groove 20 and the second groove 22, which extends on the side 26 of the second groove facing away from the electronic component to be mounted at a distance C to the second groove 22. The distance C is less than the distance B between the first groove 20 and the second groove 22 and is matched to a different fastening dimension than that of the second groove 22.

Electronic components to be mounted, whose housing has screw holes with a distance that corresponds to the distance B of the second groove 22 from the first groove 20, or of the still further groove 24 from the first groove 20, can be directly fastened by screws in the screw nuts inserted into the grooves 20, 22, 24.

In a schematic and perspective lateral view, Fig. 2 shows an angle bracket 30 for mounting, which can be matched to various fastening dimensions of electronic components to be mounted.

Electronic components to be mounted, having housings with screw holes at a distance from each other that is less than the distance B (represented in Fig. 1) of the second groove 22 from the first groove 20, or less than the distance of the still further groove 24 from the first groove 20, can be clampingly fixed in place at least on one side by the angle bracket 30 by at least one screw (not represented) engaging the screw nut introduced into the appropriate groove 22.

The angle bracket 30 has a level base plate 34 for placement against the mounting plate 10 and a clamping area 36, angled off it and made in one piece, for the clamping fixation in place of the electronic component to be mounted.

The angle bracket 30 has two elongated holes 38 and 39 extending perpendicularly (arrow D) to the extension direction (arrow A) of the second groove 22 or the still further groove 24 for receiving a screw (not represented).

In a schematic and perspective lateral view, Fig. 3 shows the mounting plate 10 in accordance with Fig. 1 with frequency converters 12 to be mounted on it and to be cooled, each of which is clampingly held on one side by an angle bracket 30 in accordance with Fig. 2.

The frequency converters, whose extension B does not match the spacing between the two grooves 20 and 22, are each screwed together on the side on the right in Fig. 3 with screws engaging the spring nuts (not represented) introduced into the groove 20. Such a screw is provided with the reference numeral 28 in Fig. 3.

On the left side in Fig. 3, the frequency converters 12 are each clamped to an additional angle bracket, one of which has the reference numeral 30. For example, a screw 32 in the elongated hole 38 of the angle bracket 30 represented, engages a spring nut (not represented) introduced into the second groove 22. The angle bracket 30 clampingly engages a protrusion 13 on the housing of the frequency converter 12. The fastening dimension which does not match the groove distances is compensated by the elongated hole.